

# HYWORTH

## X15WR and X15WRDD without platform

Model		X15WR (single scissor)		X15WRDD (double scissor)	
Load capacity/rated load	Q(kg)	1500		1000	
Load centre distance	c(mm)	500		500	
Load distance, centre of drive axle to fork	x(mm)	269/248		150	
Tyre size, front	mm	φ250×80		φ250×80+150x62x2	
Tyre size, rear	mm	φ125x82X2		φ125x82X4	
Wheels, number front rear (x=driven wheels)		1x+2/4		1x+2/4	
Forks, tilt forward/back	°	2/5		2/5	
Height, mast lowered	h1(mm)	1619/1869/2119/2369/2619	2179/2341/2499/2669	2125/2375/2625	2185/2345/2505
Free lift	h2(mm)		1575/1700/1825/2000	~ / ~ / ~	1575/1700/1825
<b>Max. lift height</b>	<b>h3(mm)</b>	<b>2000/2500/3000/3500/4000</b>	<b>4500/5000/5500/6000</b>	<b>3000/3500/4000</b>	<b>4500/5000/5500</b>
Height, mast extended	h4(mm)	2881/3381/3881/4381/4881	5381/5881/6381/6881	4035/4535/5035	5535/6035/6535
Overall length	l1(mm)	2389	2430	2535	2555
Length to face of forks	l2(mm)	1319	1360	1465	1485

Overall width	b1/b2(mm)	1220/950	1330/950	1232/950	
Fork dimensions	s/e/l(mm)	35/100/1050		35/100/1070	
Reach distance	l4(mm)	500		1200	
Aisle width, with pallet 1000×1200 crosswise	Ast(mm)	2733	2770	2593	2883
Aisle width for pallets 800×1200 lengthways	Ast(mm)	2800	2840	2967	2987
Turning radius	Wa(mm)	1588	1608	1643	1663
Travel speed, laden/unladen	Km/h	4.8/5		4.8/5	
Lift speed, laden/unladen	m/s	0.095/0.12		0.095/0.12	
Lowering speed, laden/unladen	m/s	0.2/0.15		0.2/0.15	
Battery voltage, nominal capacity k5	V/Ah	24/320(460)		24/320	
Battery weight	kg	285(360)		285	
Battery dimensions	mm	812x324x535 / 812x324x575		812x270x535	
Service weight (with battery)	kg	2250/2250/2300/2350/2350	2500/2550/2600/2650	2330/2380/2380	2530/2580/2630

AUSSIE  
FORKLIFT  
HIRE



